

## **OUTDOOR STREET**LIGHT POLE LED



## **Innovative Visual Solutions for Every Space**

Innovative LED Displays for Any SpaceDiscover our premium range of LED solutions—engineered for stunning clarity, durability, and energy efficiency. From sleek indoor panels to massive outdoor installations, rental displays, transparent screens, and flexible modules, we deliver cutting-edge performance for every application.



## **Application Range**

Widely used in large venues, stadiums, banks, post and telecommunications, government agencies, terminal, docks, stations, securities market and other market transactions, medical systems, power, and the exhibition hall a need for publicity, advertising, information release guidance and other places.

Specifications :	
Pixel pitch	4mm
LED configuration	RGB SMD
LED module size (W x H)	320mm x 160mm
LED module resolution (W x H)	80 x 40 dot
Cabinet Size (W x H)	960mm x 1440mm
Brightness	~5500 cd/m <sup>2</sup>
Grey scale	14-16
Processing	32 bit
Colors	281 trillion
Refresh Rate	1920Hz
Horizontal Viewing Angle (Degree)	140 degree
Vertical Viewing Angle (Degree)	130 degree
IP Rating (Front / Rear)	IP 65 / IP54
Control way	Synchronous
Lifetime	100,000 hrs (70% brightness)
Serviceability	Rear
Maximum power consumption	900W / meter sq.
Average power consumption	550W / meter sq.
Operation power voltage	100-240V / 50-60Hz
Operation temperature	$-20^{\circ}$ C to + $60^{\circ}$ C
Working humidity range (RH)	10-80%
Working environment	Outdoor

<sup>\*</sup> All specifications are correct at time of print, but they are subject to change without further notice. All rights are reserved to AlphalPro



www.alphalpro.com